

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/036218 A1

(51) International Patent Classification⁷: **G01N 33/543**

(21) International Application Number:
PCT/IS2003/000031

(22) International Filing Date: 17 October 2003 (17.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
6584 18 October 2002 (18.10.2002) IS

(71) Applicants and

(72) Inventors: **JOHNSEN, Kristinn** [IS/IS]; Tjarnarbolli 12,
IS-170 Seltjarnarnes (IS). **OLAFSSON, Sveinn** [IS/IS];
Vogatunga 14, IS-200 Kopavogur (IS).

(74) Agent: **A & P ARNASON**; Efstaleiti 5, IS-103 Reykjavik
(IS).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **NANOELECTRODE DEVICE FOR CHEMICAL ANALYSIS**



(57) Abstract: A device is provided with tunable affinity for molecules such as in particular macromolecules including proteins and peptides. The device comprises a substrate with a surface; a plurality of locally substantially parallel electrodes along said surface, wherein adjacent electrodes are separated by a distance in the range of about 0.1 nm to about 1 μm, such as about 0.3 nm to about 10 nm, where each of said electrodes is connected to a tunable EMF source, such that a specific electrostatic environment perpendicular to said electrodes is created, extending along the electrodes, and providing a continuous binding area for molecules in contact with the binding area. By tuning the independently tunable EMF sources a specific affinity or repulsion is obtainable for molecules with specific electrostatic properties. Also provided are methods for separating and isolating molecules with a device such as is disclosed herein.